

App'n No. 10/728,805  
Amndt. Dated March 22, 2006  
Response to Office Action dated February 08, 2006

2

## BEST AVAILABLE COPY

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1. (Currently amended) A printhead assembly for an inkjet printer, the printhead assembly comprising:
  - a support member for mounting the printhead assembly within an inkjet printer, and
  - a plurality of printhead modules mounted to the support member;
  - the support member has an overall coefficient of thermal expansion such that it changes its dimensions between its production temperature, when the printhead is assembled, and an operation temperature reached during normal operation of the printer; wherein,
  - the printhead modules are mounted to the support member at the production temperature such that they align when the printhead assembly is at the operating temperature; and
  - wherein the support member is a beam and the printhead modules include MEMS manufactured chips having at least one fiducial on each;
  - wherein,
  - the fiducials are used to misalign the printhead modules by a distance calculated from:
    - i) the difference between the coefficient of thermal expansion of the beam and the printhead chips;
    - ii) the spacing of the printhead chips along the beam; and,
    - iii) the difference between the production temperature and the operating temperature.

Pub 2004/0080512

Appia No. 10/728,805  
Amdt. Dated March 22, 2006  
Response to Office Action dated February 08, 2006

3

2. Cancelled

3. (Currently amended) A printhead assembly according to claim 2~~1~~ wherein the first component of the beam is an outer metal shell, and the second component of the beam is a core of silicon within the outer metal shell.

4. (Original) A printhead assembly according to claim 3 wherein the beam is adapted to allow limited relative movement between the silicon core and the metal shell.

5. (Original) A printhead assembly according to claim 4 wherein the beam includes an elastomeric layer interposed between the silicon core and metal shell.

6 (Original) A printhead assembly according to claim 3 wherein the outer shell is formed from laminated layers of at least two different metals.

7. (Original) A printhead assembly according to claim 1 wherein the printhead is a pagewidth printhead for printing across the width of a page simultaneously.